DEL DL500F



Suitable segments

- Construction
- Highways
- Tool hire
- Builders merchants
- Horticulture
- Local authorities
- Railways

Move more with confidence - our high-strength, lightweight column lift boosts payload capacity, keeps your vehicles running longer, and ensures safer, smoother operation – for maximum uptime and ROI.

Optimised performance & payload

A lightweight, high-strength design protects payload capacity, enabling more cargo per trip for all your 3.5 tonne vehicles. The stable platform supports efficient multi-load handling, and quick-acting hydraulics combined with a level-ride platform ensure smooth, safe operation in all conditions.

Maximum uptime & reliability

The simple, circuit-card-free electrical system and pre-drilled columns ensure quick installation and easy maintenance, while the bolt-together design allows fast component replacement to keep costs low. Backed by our extensive service network, your vehicles stay operational with minimal downtime.

Safe & easy operation

Featuring a torsion-assisted platform with flush lock, safety catch design and anti-tilt system, our lifts offer effortless and secure handling. A quiet chain/roller system enhances operator comfort. Safety fence options and full EU compliance protect operators and bystanders. Engineered for flatbed / dropside vehicles, our lifts promise greater driver visibility and reduced wind drag for improved safety and efficiency.

Long-term value

Built for lasting performance and a lower environmental impact with optional solar panels tripling battery life, advanced galvanising, optimised steel and aluminium structures, and a high capacity-to-weight ratio boosting fuel efficiency – for a lift that runs cleaner, lasts longer (7-10 years), and delivers maximum uptime and ROI.

DL500F Specifications	
Column width	1780 - 2260 mm in nine standard widths*
Platform depth	850 - 1105 mm*
Lifting capacity	500 kg
Bed height min/max	800 mm/1060 mm
Platform	Aluminium
Weight of complete lift	140 kg
Max vehicle weight	3.5 t

*See specification sheet for details



Options

Safety	Pair detachable side guards Fixed ramps and trolley stops Flashing lights Switch over control on dual control
Operation	Standard columns Short column application Battery guard Dual controls, with or without Wanderlead (spiral cable)
Material	Platform in anodised aluminium
Installation	Plug-and-play installation Factory body fitting kit
Warranty	12 months parts and labour as standard Extended warranty

PB-DEL-DL500F-EN-EU_260331