

DEL DA1500

Suitable segments

- Vehicle rental
- Laundries
- Parcel deliveries
- Bakeries
- Home delivery services



Experience maximum uptime, safety, and durability with our tuckunder lifts - delivering powerful lifting performance, low-maintenance efficiency, and all-weather reliability in a convenient, eco-smart design that keeps your fleet operating smoothly and cost-effectively for longer.

Powerful, efficient tuckunder design

Our tuckunder lift deliver a 1500 kg lifting capacity for 7.5+ tonne vehicles, pairing a lightweight yet robust galvanised steel frame, fully aluminium platform and greaseless heavy-duty bearings to cut maintenance costs, while the lift stows neatly underneath the vehicle for easy dock loading and occasional-use operations – maximising uptime, payload and overall efficiency.

All-weather performance & safety

The stable platform with quick-acting hydraulics ensures smooth, safe operation in all conditions. With roll stops and

optional safety fences and guards, every lift delivers effortless handling, full EU compliance, and superior protection for operators and bystanders.

Maximum uptime & reliability

The preassembled product features a simple, circuit-card-free electrical system and optional pre-drilled mounting brackets for quick installation and easy maintenance. Backed by our extensive service network, your vehicles stay operational with minimal downtime.

Long-term value

Built for lasting performance and a lower environmental impact with optional solar panels tripling battery life, optimised recyclable materials, energy-efficient, low-emission coating, and a high capacity-to-weight ratio boosting fuel efficiency. Your lift runs cleaner, lasts longer (7-10 years), and delivers maximum uptime and ROI.

DA1500 Specifications	
Platform width	2135 mm
Platform depth	1425 mm including 205 mm ramp
Lifting capacity	1500 kg
Bed height min/max	1190 - 1440 mm
Platform	Aluminium with steel support
Weight of complete lift	360 kg
Max vehicle weight	26 t

Options

Safety	Detachable fences Fixed ramps and trolley stops Flashing lights Switch over control on dual control
Operation	Battery guard Dual controls, with or without Wanderlead (spiral cables)
Material	Platform in anodised aluminium Galvanised steel structure
Installation	Floor plate included
Warranty	12 months parts and labour as standard Three year warranty against corrosion on the frame Extended warranty

