

# DEL TL1000



## Suitable segments

- Vehicle rental/leasing
- Home delivery
- Traffic management
- Food and beverage
- Laundry
- Retail
- Construction

Our trimloader column tail lift delivers superior versatility, durability, and efficiency across a range of vehicles – combining all-weather safety and performance, low-maintenance reliability, and sustainable design to maximise payload, uptime, and long-term ROI.

### Versatile lifting capacity

Our trimloader column tail lift is suitable for a wide range of vehicles from light (3.5 tonnes, 500 kg lift) to heavy-duty (15 tonnes, 1,000 kg lift) – making it adaptable to any fleet.

### All-weather performance & safety

Combines robust engineering with a lightweight design, maximising payload capacity. The stable, level-ride platform with quick-acting hydraulics ensures smooth, safe operation in all conditions. With a torsion-assisted platform, anti-tilt system, and safety fence options, every lift delivers effortless handling, full EU compliance, and superior protection for operators and bystanders.

### Maximum uptime & reliability

The simple, circuit-card-free electrical system, pre-drilled columns and mounting brackets, and greasable long-life sprocket pins ensure quick installation and easy maintenance, while the bolt-together design allows fast component replacement to keep costs low. Backed by our extensive service network, your vehicles stay operational with minimal downtime.



### Future-ready flexibility

Designed to evolve with customer needs - optional retrofit safety upgrades such as fences and hinged side ramps can be easily added.

### Long-term value

Built for lasting performance and a lower environmental impact with optional solar panels tripling battery life, advanced galvanising, optimised steel and aluminium structures, and a high capacity-to-weight ratio boosting fuel efficiency – for a lift that runs cleaner, lasts longer (7-10 years), and delivers maximum uptime and ROI.

#### TL1000 Specifications

Platform width	2120 - 2515 mm
Platform depth	950 - 1550 mm
Lifting capacity	1000 kg (option 500 kg and 750 kg)
Bed height min/max	900 - 1320 mm
Platform	Aluminium
Weight of complete lift	250 kg
Max vehicle weight	26 t

### Options

Safety	Trolley stops Anti-tilt catch Platform safety catch Hinged side or rear ramps Auto erect fences Dual mode fences Detachable fences Wrap around fences Stow light indicator Platform lights Two handed control
Operation	Pre-driller bolt on columns Adjustable bolt-on underrun bar Battery guard Solar panel kit
Maintenance	Bolt together design allows easier service/repairs (most applications) Greasable sprocket pins Power pack and hydraulics enclosed inside tail lift beam for added protection Wear pads to minimise maintenance
Material	Galvanised steel lift frame Aluminium platform Aluminium platform with mesh window for dropside applications Anti-slip overlay for tail lift platform
Installation	Extended power cables Barn door application

PB-DEL-TL1000-EN+EU\_260331