

MOFFETT LR70





TECHNICAL INFORMATION:

LR70



MOFFETT LR70



MODEL		LR70
	TYPE	LIVE RECEIVING
1	CAPACITY @ 24" LOAD CENTER (48" LC)	7000 lbs (3500 lbs)
2	DIESEL ENGINE	72 hp
3	ENGINE EMISSION COMPLIANCE	EPA Tier4 Final
4	MAXIMUM RPM	3000 rpm
5	ELECTRICAL SYSTEM	12 Volt
6	DRIVE WHEELS	3
7	STEERING	Hydrostatic
8	TIRE SIZE (SKID STEER)	27 x 10 - 12, 20-PLY
9	TIRE OUTSIDE DIAMETER	27"
10	TIRE WIDTH	10"
11	MAXIMUM SPEED	10 mph
12	MAXIMUM GRADABILITY	15%
13	TURNING RADIUS	104"
14	UNLADEN WEIGHT	12,500 lbs
15	WORKING PRESSURE FOR ATTACHMENTS	2500 psi
16	TILT OF MAST (FORWARD/BACK)	10° / 8°
17	SIDESHIFT	5"
18	FORK SECTION	74" x 5" x 1.75"
19	ROTATOR (Optional) ROTATION ANGLE	5°
A	OVERHEAD GUARD HEIGHT	104"
B	FORK CARRIAGE WIDTH	48.25"
C	TRACK - FRONT	79.5"
D	OVERALL WIDTH	89.5"
E	OVERALL LENGTH	178"
F	WHEEL BASE	75"
G	C. OF G. FROM FORK FACE	57"
H1	LIFT HEIGHT	132"
H2	MAST HEIGHT (COLLAPSED)	103"
H3	MAST HEIGHT (RAISED)	178"
J	GROUND CLEARANCE	13.5"
K	FACE OF FORK TO CENTER OF FRONT TIRE	13.5"
L	ANSI STANDARD	B56.6

NOTES: The above specifications are not binding upon the manufacturer and may be changed without prior notice.
Weights may vary depending on tire and/or fork option.

© Copyright 2015 Hiab USA Inc. All rights reserved. No part of this document may be reproduced without the prior written consent of Hiab USA Inc.