

ZEPRO

Z2500/ZN2500

Suitable segments

- Vehicle rental
- Food and Beverage
- Distribution
- Laundry delivery
- Construction material delivery
- Home delivery services



Engineered for maximum power and performance, The ZEPRO Z2500/ZN2500 flagship tail lift features advanced hydraulics, double-acting tilt cylinders and robust components promising exceptional strength, stability, durability and all-weather efficiency for heavy duty operators – maximising uptime and ROI in the toughest environments.

Powerful, reliable performance

Delivers exceptional lifting strength and durability for trucks and trailers through advanced hydraulics and robust components designed for everyday heavy-duty use

All-weather efficiency & protection

Double-acting tilt cylinders maintain consistent speed, even in extreme cold, to maximise delivery efficiency. Integrated hydraulic and control systems stay shielded from the elements for long-term reliability and easier maintenance.

Z2500/ZN2500 Specifications	
Platform width	Up to 2580 mm*
Platform depth	Up to 2500 mm
Lifting capacity	2500 kg
Bed height max	Up to 1710 mm
Voltage	12V or 24V
Platform	Steel
Weight of complete lift	From 716 kg (636 kg for ZN2500)
Max vehicle weight	26 t

*See specification sheet for details



Fast, flexible installation

Bolt-on brackets and universal mounting kits for major truck brands (including Volvo, Scania, Mercedes and Iveco) enable quick, easy installation in under 4 hours.

Robust, customisable design

Strong steel or aluminium platforms in multiple configurations ensure secure handling, complemented by ergonomic controls that boost operator comfort and safety.

Long-term value

Delivering lasting corrosion protection with premium powder coating. Featuring durable hydraulics with a ClearOil long-life filter, optional solar panels, and tested for 30,000 lift cycles (12 years), it cuts downtime by up to 66% and maximises ROI.

Options

Safety	Trolley roll stops in different configurations Warning lights on platform Extra slip resistant platforms VDHH control override Toe guard with guide bar installation
Operation	PIEK platform coating Electrical auto-tilt* Radio control* ADR II & III Stainless steel wear protection on platform for extended lift
Material	Galvanized steel structure
Installation	Mounting brackets pre-drilled for all major trucks available Width adjustable mounting brackets Platform as rear door with ZEPRO's heavy-duty seal system

*Also retrofittable

ZN2500

Option for trailer installation available with arms designed for trailer chassis and clamping brackets.