

Company Name:	Date:		
Order Number:	Quantity required:		
Deliver Lift Collect Lift from Del	Delivery Date Required:		
Do you have a forklift to unload?			
Yes No, require DEL to provide a For	'k Lift		
Delivery Address			
Company Name:	Street Address:		
Post Code:	City:		
Vehicle Details			
Rigid Trailer Chassis Mass:			
Box Body Curtainsider Dropside			
Suspension Type:			
Steel Air			
Dimension A (Unladen Vehicle Floor Height):	ــــــ mm (Max 1320mm)		
Dimension A (Laden Vehicle Floor Height):	mm		
Dimension B (Overall Width of Vehicle):	mm		
Dimension C (Loading Aperture):	mm		
Dimension D (Width of Corner Post):	mm		
Vehicle Overhang mm			
Tail Lift Width required: (Please Note: Column Centre	s are 63mm less than the sizes below)		
2120mm 2210mm 2310mm 2413mm			
Vehicle Voltage: (Heavy Duty Battery required on a 12V ve	ehicle, in some cases SWL needs to be reduced to 750KG)		
12v* 24v			
Underun & Bracing requirement:			
R58-03 Underun & Bracing No Underun & Br	racing		

Specification Sheet for TL1000GP (Mesh) Range



Tail Lift Details

Lift Capacity:			
500kg	750kg	1000kg	
Platform Specifica	tion:		
950mm + 250m	m Fixed Ramp ir	nc Trolley Stops	
1250mm + 250r	nm Fixed Ramp	inc Trolley Stops	
Control Setup:			
Dual Fixed Con	itrols	Single External Wanderlead	d Internal Hard Wired Wanderlead and Fixed External Control
Slimline Fixed External Control & Internal Fixed Control			
Internal Control B	racket:		
Bracket with De	eflector Plate	Bracket with No Deflector F	Plate
Tail Lift Isolator: (Not required with Single Detachable Wanderlead)			
Cab Switch		Red Key Isolator	
Cable Options:			
28' Battery Cables (Standard) 35' Battery Cables			
Fence Type:			
Auto Erect Fen	ces	Wrap Around Fences	Dual Mode Fences
Options:			
Battery Guard		Flashing Lights	Left Hand Drive
Stow Light India	cator	Two Handed External Contr	rol
Warranty options: (12 month Warranty as standard)			
2 Year Warranty 3 Year Warranty 4 Year Warranty 5 Year Warranty			