



EFFER 230 D

TECHNICAL SPECIFICATION

EFFER 230 D

TECHNICAL DATA	230 D B-2	230 D B-3	230 D B-4	230 D E-5	230 D E-6
Max. lifting capacity (ft-lbs)	147 810	143 620	137 550	137 260	134 580
Outreach, hydraulic extensions (ft)	27′ 11″	41′ 4″	42′ 5″	49′ 6″	56′ 10″
Outreach / lifting capacity (ft-lbs)	11' 2" - 13 010 15' 1" - 9 810 21' 0" - 6 940 27' 7" - 5 300 - - -	11' 6" - 12 570 15' 5" - 9 150 21' 0" - 6 610 27' 7" - 4 940 34' 5" - 2 920 - -	11' 6" - 12 130 15' 5" - 8 930 21' 0" - 6 280 27' 7" - 4 630 34' 5" - 3 620 41' 4" - 3 000 -	11' 10" - 11 680 16' 1" - 8 490 21' 8" - 6 060 28' 3" - 4 410 35' 1" - 3 400 42' 0" - 2 730 49' 3" - 2 340	11' 10" - 11 460 16' 1" - 8 380 22' 0" - 5 730 28' 3" - 4 140 34' 9" - 3 170 41' 8" - 2 560 48' 11" - 2 090 56' 5" - 1 790
Slewing angle (°)	415	415	415	415	415
Height in folded position (in)	89	90	90	89	89
Width in folded position (in)	96	97	97	98	98
Installation space needed (in)	42	59	44	42	46
Weight, "standard" crane without stabilizers (lbs)	4 460	4 410	4 720	5 250	4 530
Weight, stabilizer equipment (lbs)	600 - 940	600 - 940	600 - 940	600 - 940	600 - 940
Weight, jib (lbs)	-	-		-	-


Features

- · D-Drive remote control system
- VSL: Variable Stability Limit (Optional)
- · LSS-V: Load Stability System
- 1 Year warranty All inclusive
- · 3 Year warranty Structural

- · SAF: Semi Automatic Folding
- HiConnect
- nDurance[™] nano technology coating







Hiab is a leading provider of smart and sustainable load handling solutions. We are committed to delivering the best customer experience every day with the most engaged people and partners. Hiab's premium equipment includes HIAB, EFFER and ARGOS loader cranes, MOFFETT and PRINCETON truck mounted forklifts, LOGLIFT forestry cranes, JONSERED recycling cranes, MULTILIFT skiploaders and hooklifts, GALFAB roll-off cable hoists, and tail lifts under the ZEPRO, DEL and WALTCO brands. As the industry pioneer, Hiab continues to make load handling smarter, safer and more sustainable to build a better tomorrow.



Hiab USA, Inc. 12233 Williams Rd Perrysburg, 43551 OH USA tel. +419 482 6000