

DEL WB300

Suitable segments

- Local councils
- Waste recycling
- Food waste recycling



Boost operational efficiency with our compact and versatile bin lift – delivering powerful, lightweight performance, easy installations and maintenance, and long-lasting reliability for maximum payload, uptime, and ROI.

Compact, efficient & versatile

With a 300 kg lifting capacity for 3.5+ tonne vehicles, our robust bin lifts deliver powerful, lightweight performance across a wide range of tip heights (1670-3400 mm). Ideal for reduced-access routes, it lifts 240-360L BSEN 840 bins with hydraulic power from the vehicle battery or power take off system – maximising operational efficiency.

All-weather performance & safety

The robust and durable lift frame design with quick-acting hydraulics ensures smooth, safe operation in all conditions.

WB300 Specifications

Column width	660 mm
Lifting capacity	300 kg
Tipping height min/max	3260/3400 mm*
Weight of complete lift	From 300 kg
Max vehicle weight	26 t

*See specification sheet for details

Options

Safety	Visual warning Audible warning Two-handed control
Operation	Roof mechanism
Material	Galvanised steel in frames
Installation	Pre-drilled columns
Warrenty	12 months parts and labour as standard Extended warranty

With optional audible and visual warning systems and two-handed controls, every lift delivers effortless handling, full EU compliance, and superior protection for operators and bystanders.

Maximum uptime & reliability

The simple, circuit-card-free electrical system and pre-assembled lift with pre-drilled columns ensure quick installation and easy maintenance. Backed by our extensive service network, your vehicles stay operational with minimal downtime.

Long-term value

Built for lasting performance and a lower environmental impact with optional solar panels tripling battery life, advanced galvanising, optimised steel structures, and a high capacity-to-weight ratio boosting fuel efficiency – for a lift that runs cleaner, lasts longer (7-10 years), and delivers maximum uptime and ROI.



PB-DEL-WB300-EN-EU_260331